

Unit Ref	Nom Spd	dBA	Volume M3/s @ Pa Pressure									Input Pr Kw	Current FLC	Amps SC	Speed Cont
			FID	25	50	75	100	125	150	175	200				
RV-ZAP-315-21	2650	61	0.998	0.969	0.990	0.908	0.870	0.823	0.779	0.723		0.47	2.1	6	A
RV-ZAP-315-41	1360	48	0.541	0.455	0.364	0.273	0.167	0.068				0.13	0.64	1.1	B
RV-ZAP-315-61	880	40	0.356	0.048								0.07	0.37	0.7	B
RV-ZAP-350-41	1330	53	0.770	0.694	0.437	0.314	0.238	0.119				0.19	0.84	1.45	B
RV-ZAP-350-61	910	44	0.355	0.048								0.1	0.5	100	B
RV-ZAP-400-41	1350	58	1.207	0.998	0.931	0.627	0.456	0.295				0.29	1.45	2.4	A
RV-ZAP-400-61	940	48	0.865	0.703	0.204							0.13	0.6	1.4	B
RV-ZAP-450-41	1370	58	1.463	1.388	1.307	1.199	1.045	0.618	0.504			0.36	1.6	3.6	A
RV-ZAP-450-61	930	49	0.999	0.834	0.276	0.076						0.17	0.75	1.5	B
RV-ZAP-500-41	1290	60	2.420	2.300	2.130	1.970	1.760	1.550				0.51	2.3	4.5	C
RV-ZAP-500-61	920	54	1.455	1.235	0.542	0.119						0.2	0.96	2.7	A
RV-ZAP-560-41	1300	68	2.850	2.626	2.478	2.289	2.071	1.710	1.245	0.950		1.6	7.5	15	C1
RV-ZAP-560-61	880	55	1.748	1.387	0.874	0.475						0.43	1.95	4.6	A
RV-ZAP-630-61	880	59	2.850	2.565	2.328	1.235	0.831					0.6	2.7	5.3	A
RV-ZAP-630-81	650	55	2.100	1.520	0.371							0.32	1.45	3.1	A
RV-ZAP-710-61	850	61	3.468	3.206	2.921	2.280	1.499					0.89	4.1	8	C

Three Phase Units

RV-ZAP315-23	2690	64	0.950	0.922	0.892	0.855	0.817	0.777	0.724	0.650		0.51	0.79	2.4	D
RV-ZAP315-43	1390	48	0.541	0.455	0.380	0.289	0.174	0.071				0.11	0.27	0.85	D
RV-ZAP315-63	900	40	0.308	0.038								0.05	0.14	0.45	D
RV-ZAP350-43	1390	54	0.779	0.704	0.475	0.362	0.261	0.138				0.18	0.39	1.35	D
RV-ZAP350-63	910	44	0.355	0.475								0.09	0.25	0.75	D
RV-ZAP-400-43	1380	59	1.211	1.045	0.931	0.627	0.456	0.295				0.28	0.6	2.1	D
RV-ZAP-400-63	920	48	0.865	0.703	0.214							0.11	0.28	0.9	D
RV-ZAP-450-43	1390	58	1.463	1.388	1.307	1.199	1.045	0.618	0.504			0.36	0.75	2.6	D
RV-ZAP-450-63	940	49	0.999	0.834	0.276	0.076						0.125	0.35	1	D
RV-ZAP-500-43	1380	61	2.033	1.900	1.748	1.587	1.425	0.855	0.665			0.55	1.05	3.7	D
RV-ZAP-500-63	920	52	1.455	1.235	0.589	0.133						0.2	0.56	1.5	D
RV-ZAP-560-43	1300	63	2.660	2.489	2.280	2.024	1.758	1.425	1.083	0.855		1	1.8	7	E
RV-ZAP-560-63	860	55	1.672	1.188	0.713	0.380						0.39	0.81	1.75	D
RV-ZAP-630-43	1360	70	4.180	3.954	3.800	3.610	3.373	3.111	2.280	1.957	1.734	1.9	3.2	14	D
RV-ZAP-630-63	880	60	2.850	2.565	2.328	1.235	0.831					0.7	1.5	3.6	D
RV-ZAP-630-83	630	55	2.100	1.520	0.371							0.31	0.65	2	D
RV-ZAP-710-63	890	62	3.468	3.206	2.969	2.541	1.710					0.89	1.8	6.4	D
RV-ZAP-710-83	640	55	2.413	1.815	1.140	0.380						0.42	1.1	3.3	D
RV-ZAP-800-63	900	62	5.040	4.820	4.550	4.190	3.700	1.990	1.728	1.476		1.4	2.7	9.8	E

1Ph Speed controllers

A: SC3 \ RTRE3

B: SC1.5 \ RTRE 1.5

C: SC5 \ RTRE5

C1: RTRE7

3 Ph Speed controllers

D: RTRD2

E: RTRD4

F: RTRD7